
HYUNDAI IT CO., LTD.

HYUNDAI IT CO., LTD.

OUTDOOR DIGITAL SIGNAGE



KEY FEATURES

- Special DOOH LCD Panel
- USB Plug & Play (JPG & MP4)
- All Weather Capable
- Sunlight Readable
- Air-Looping System
- Auto Brightness Control
- Remote Control (RS232)
- Easy to Service with Front Door Open
- Cabinet Housing Color : Black (RAL9005)
- Slim & Light.



Broadcast your branding with **HYUNDAI IT Digital Signage!**

HYUNDAI IT's outdoor displays represent state-of-the-art display technology for any outdoor environment. Meeting the highest industrial standards they are provide a high degree of operational reliability and superior quality image, which are essential preconditions for attracting the attention of your target audience.



SPECIFICATIONS

| | Model | Q467MSG |
|--------------------------|---------------------------------------|--|
| Panel | Screen Size (diagonal) | 46" |
| | Active Display Area (inch mm) | 40.08 x 22.54 1018.08 x 572.67 |
| | Resolution | 1920 x 1080 |
| | Aspect Ratio | 16:9 |
| | Display Colors | 10bit (8bit+FRC), 1073.3M |
| | Brightness (cd/m ² ; typ.) | 2500 |
| | Contrast Ratio | 4000:1 |
| | Response Time (ms; GTG) | 8 |
| | Viewing Angle | 178°/178° |
| | Lifetime (hours) | 70,000 |
| | Backlight type | LED |
| Input | | 1xVGA 3xHDMI 1xPC audio 1xRS232C 1x IR 1xUSB(Media Player) |
| Media Player (USB) | Movie | MPEG-2 MPEG-4 |
| | Photo | JPEG PNG BMP |
| | Music | MP3 |
| Power | Operating Voltage | 100 – 240VAC |
| | Consumption (typ.) | 300W (Without PC) |
| | Consumption per nits (max.) | 0.12W |
| | Heating Unit | Typ: 650W (Max: 850W) |
| Features | Auto Cooling System | Yes |
| | Auto Heating System | Yes |
| | Tempered Glass | 8mm (AR) |
| | Anti Reflection Coating | Yes |
| | Auto Brightness Sensor | Yes |
| Operation | Temperature (°C) | -30 ~ 50 |
| | Humidity (%) | 20 - 80 |
| | Storage (°C) | -40 ~ 60 |
| | OSD Language | 12 Lang |
| Approvals | Ingress Protection | IP65 |
| Dimension | Set (W x H x D), inch mm | 46.06 x 28.74 x 7.20 1170 x 730 x 183 (with Wall Frame) |
| Weight | Set (lb kg) | 176.37 80 (TBD) |
| Mounting | | Wall mounting (Built-in) |
| Computer | | Option |

Specifications and design are subject to change without notice. See our website for detailed information.

HEAD OFFICE - HYUNDAI IT CO., LTD. 5F, 36, Sangil-ro 10-gil, Gangdong-gu, Seoul, 05288 Korea Tel. +82 70 7008 0151 E-mail: ssoh@hyundaiit.com www.hyundaiit.com

HYUNDAI IT AMERICA TECH CORP 2033 Gateway Place 5th Floor San Jose, CA 95110, USA Tel. +1 408 627 4729 email : sales@hyundaita.com www.hyundaiit.com

OUTDOOR DIGITAL SIGNAGE

CLASS

46″

Q467MSG

FEATURES

All Weather Capable

Equipped with an intelligent cooling and heating system, HYUNDAI IT's Outdoor Displays are well suited for withstanding any weather conditions from -30°C to +50°C.

Sunlight Readable

HYUNDAI IT provides special displays which are based on the Optical Bonding for installatons in environment with the birghtest lightning conditions. Make your messages and images clear and readable under even bright sunlight.

Cost Effective Media Player

HYUNDAI IT's display serves in-built media player enables to play various range of content including video, images and photos.

Thanks to this solution, no need for an additional media player for cost and space efficiency.

Display : 150 [5.91] 1170 730 with WallFrame : 183

HYUNDAI IBT GMBH

Carl-Zeiss-Str. 9 / 55129 Mainz, Germany Tel. +49(0) 6131 275 5350 email : info@hyundaiit.eu www.hyundaiit.eu

DIMENSIONS

UPDATE: DEC. 2021

[Unit: mm[inch]]