HYUNDAI

HYUNDAI

OUTDOOR DIGITAL SIGNAGE

KIOSK PORTRAIT TYPE SCREEN



Broadcast your branding with Hyundai Digital Signage!

HYUNDAI's Outdoor Digital Signage represents state-of-art display technology for any outdoor environment. Meeting the highest industrial standards they are provide a high degree of operational reliability and superior quality image, which are essential preconditions for attracting the attention of your target audience.

KEY FEATURES

- Special DOOH LCD Panel
- USB Plug & Play (JPG & MP4)
- All Weather Capable (IP66)
- Sunlight Readable
- Auto Brightness Control
- Remote Control (RS232)
- Capacitive Touch applied.
- Easy to Service with Front Door Open
- Side Frame : Aluminum Titanium Gray Color
- Top & Bottom Frame : Aluminum Black Color

• Glass & Body : Black Color(RAL9005)



SPECIFICATIONS

	Model	Q557SSI
	Screen Size (diagonal)	55″
Panel	Active Display Area (inch mm)	47.62 x 26.787 1209.6 x 680.4
	Resolution	1920 x 1080
	Aspect Ratio	16:9
	Display Colors	1.07B
	Brightness (cd/m ² ; typ.)	2,500
	Contrast Ratio	4,000:1
	Response Time (ms; GTG)	8
	Viewing Angle	178° / 178°
	Lifetime (hours)	60,000
	Backlight type	LED
Touch Screen	Response Time (ms)	50 ~ 100
	Interface	USB 2.0
	Available Touch Point	1~10
	Touch Intensity	Permanent (Protected by glass)
	Detection Method	РСТ
Input		1xVGA 3xHDMI 1xPC audio 1xRS232C 1x IR 1xUSB(Media Player)
Media Player (USB)	Movie	MPEG-2 MPEG-4
	Photo	JPEG PNG BMP
	Music	MP3
Power	Operating Voltage	100 - 240 VAC
	Consumption (typ.)	440W (Without PC)
	Consumption per nits (max.)	0.176 W
	Heating Unit	Typ: 600W (Max: 850W)
Features	Auto Cooling System	Yes
	Auto Heating System	Yes
	Tempered Glass (Thickness)	8mm (AR)
	Anti Reflection Coating	Yes
	Auto Brightness Sensor	Yes
	Speaker	Yes (10W x 10W)
	USB WebCAM	Option
Operation	Temperature (°C)	-30 ~ 50
	Humidity (%)	20 - 90
	Storage (°C)	-40 ~ 60
	OSD Language	12 Lang
Approvals	Ingress Protection	IP66
	Glass Protection	IK10
Dimension	Set (W x H x D), inch mm	37.87 x 88.17 x 6.30 962 x 2239.7 x 160
Weight	Set (lb kg)	407.86 185
Mounting (Bottom mounting)		M10 wedge anchor (6 pcs)

Specifications and design are subject to change without notice. See our website for detailed information.

HEAD OFFICE - HYUNDAI IT CO., LTD.

5F, 36, Sangil-ro 10-gil, Gangdong-gu, Seoul, 05288 Korea Tel. +82 70 7008 0151 E-mail: ssoh@hyundaiit.com www.hyundaiit.com

HYUNDAI IT AMERICA TECH CORP 2033 Gateway Place 5th Floor San Jose, CA 95110, USA

Tel. +1 408 627 4729 email : sales@hyundaita.com www.hyundaiit.com

OUTDOOR DIGITAL SIGNAGE

CLASS

55″

O557SSI

FEATURES

All Weather Capable

Equipped with an intelligent cooling and heating system, HYUNDAI's Outdoor Displays are well suited for withstanding any weather conditions from -30° C to $+50^{\circ}$ C.

Sunlight Readable

DIMENSIONS

HYUNDAI provides special displays which are based on the Optical Bonding for installatons in environment with the birghtest lightning conditions. Make your messages and images clear and readable under even bright sunlight.

Cost Effective Media Player

HYUNDAI IT's display serves in-built media player enables to play various range of content including video, images and photos.

Thanks to this solution, no need for an additional media player for cost and space efficiency.

[unit: mm | [inch]] S • 1 • 1 962 [37.87] 160 239.7 88.171



UPDATE: JUN. 2023

HYUNDAI IBT GMBH Carl-Zeiss-Str. 9 / 55129 Mainz, Germany

Tel. +49(0) 6131 275 5350 email : info@hyundaiit.eu www.hyundaiit.eu