HYUNDAI IT CO., LTD.

OUTDOOR DIGITAL SIGNAGE

LARGE SIZE FORMAT APPLIED SCREEN

CLASS

MODEL

86"

Q867MSI

KEY FEATURES

- Special DOOH LCD Panel
- USB Plug & Play (JPG & MP4)
- All Weather Capable
- Sunlight Readable
- · Air-Looping System
- Auto Brightness Control
- Easy to Service with Front Door Open
- Cabinet Housing Color: Black (RAL9005)
- Capacitive Touch applied
- Slim & Light.



Broadcast your branding with HYUNDAI IT Digital Signage!

HYUNDAI IT's outdoor displays represent state-of-the-art display technology for any outdoor environment. Meeting the highest industrial standards they are provide a high degree of operational reliability and superior quality image, which are essential preconditions for attracting the attention of your target audience.



HYUNDAI IT CO., LTD.

OUTDOOR D	OUTDOOR DIGITAL SIGNAGE		
MODEL	CLASS		
Q867MSI	86"		

SPECIFICATIONS

Panel Acti Res Asp Disy Panel Brig Cor Res Vier Life Bac Inte Touch Screen Ava Tou Det Input Media Player (USB) Mu Power Cor Cor	een Size (diagonal) ive Display Area (inch mm) olution sect Ratio play Colors ghtness (cd/m²; typ.) ntrast Ratio ponse Time (ms; GTG) wing Angle ettime (hours) eklight type ponse Time (ms) erface oilable Touch Point ch Intensity section Method	86" 74.608 x 41.613 1895.04 x 1065.96 3840 x 2160 16 : 9 1.07B 3,500 1,200:1 8 178° / 178° 50,000 LED 16 USB 2.0 1 ~ 10 Permanent (protected by glass) PCT
Panel Res Asp Disp Cor Res Vier Life Bac Inte Touch Screen Ava Tou Det Input Media Pho (USB) Mu Ope Cor	polution pect Ratio play Colors ghtness (cd/m²; typ.) ntrast Ratio ponse Time (ms; GTG) wing Angle time (hours) cklight type ponse Time (ms) erface silable Touch Point ch Intensity ection Method	3840 x 2160 16 : 9 1.07B 3,500 1,200:1 8 178° / 178° 50,000 LED 16 USB 2.0 1 ~ 10 Permanent (protected by glass)
Panel Asp Dist Dist Cor Res Vier Life Bac Inte Touch Screen Ava Tou Det Input Media Player (USB) Mu: Ope Cor Cor	play Colors play Colors phrass (cd/m²; typ.) phrast Ratio ponse Time (ms; GTG) wing Angle titime (hours) cklight type ponse Time (ms) erface ailable Touch Point ch Intensity eection Method	16:9 1.07B 3,500 1,200:1 8 178° / 178° 50,000 LED 16 USB 2.0 1 ~ 10 Permanent (protected by glass)
Panel Brig Cor Res Vier Life Bac Touch Screen Ava Tou Det Input Media Player (USB) Mu: Ope Cor Cor	play Colors ghtness (cd/m²; typ.) ntrast Ratio sponse Time (ms; GTG) wing Angle ettime (hours) kklight type sponse Time (ms) erface ailable Touch Point ch Intensity section Method	1.07B 3,500 1,200:1 8 178° / 178° 50,000 LED 16 USB 2.0 1 ~ 10 Permanent (protected by glass)
Panel Brig Cor Res Vier Life Bac Inte Touch Screen Ava Tou Det Input Media Player (USB) Mu Ope Cor Cor	htrast Ratio ponse Time (ms; GTG) wing Angle witime (hours) sklight type ponse Time (ms) erface ailable Touch Point ch Intensity ection Method	3,500 1,200:1 8 178° / 178° 50,000 LED 16 USB 2.0 1 ~ 10 Permanent (protected by glass)
Res Vier Life Bac Touch Screen Ava Tou Det Input Media Phor (USB) Mu Ope Cor Cor	ntrast Ratio uponse Time (ms; GTG) wing Angle ettime (hours) Eklight type uponse Time (ms) erface eilable Touch Point ech Intensity eection Method	1,200:1 8 178° / 178° 50,000 LED 16 USB 2.0 1 ~ 10 Permanent (protected by glass)
Res Viet Life Bac Res Inte Touch Screen Ava Tou Det Input Media Player (USB) Mu Ope Cor Cor	ponse Time (ms; GTG) wing Angle time (hours) cklight type ponse Time (ms) erface ailable Touch Point ch Intensity eection Method	8 178° / 178° 50,000 LED 16 USB 2.0 1 ~ 10 Permanent (protected by glass)
Vier Life Bac Res Inte Touch Screen Ava Tou Det Input Media Player (USB) Mu: Cor Cor	wing Angle time (hours) kklight type ponse Time (ms) erface ailable Touch Point ch Intensity ection Method	178° / 178° 50,000 LED 16 USB 2.0 1 ~ 10 Permanent (protected by glass)
Life Bac Res Inte Touch Screen Ava Tou Det Input Media Player (USB) Mu Ope Cor	ctime (hours) cklight type sponse Time (ms) erface cillable Touch Point cch Intensity section Method	50,000 LED 16 USB 2.0 1 ~ 10 Permanent (protected by glass)
Res Inte Touch Screen Ava Tou Det Input Media Player (USB) Mu Ope Cor Cor	cklight type ponse Time (ms) erface illable Touch Point cch Intensity rection Method	LED 16 USB 2.0 1 ~ 10 Permanent (protected by glass)
Touch Screen Ava Touch	ponse Time (ms) erface silable Touch Point uch Intensity ection Method	16 USB 2.0 1 ~ 10 Permanent (protected by glass)
Interval and Inter	orface ailable Touch Point ch Intensity ection Method	USB 2.0 1 ~ 10 Permanent (protected by glass)
Touch Screen Ava Tou Det Input Media Player (USB) Mu: Ope Cor Cor	ailable Touch Point ch Intensity section Method	1 ~ 10 Permanent (protected by glass)
Input Media Mor Phor (USB) Mu Oper Corr Tou	ch Intensity ection Method	Permanent (protected by glass)
Det Input Media Mo' Player (USB) Mu Ope Cor Cor	rection Method	
Input Media Mo' Player Pho (USB) Mu: Ope Cor Cor		PCT
Media Player (USB) Mu: Ope Corr Power Corr		
Media Player (USB) Mu: Ope Cor Power Cor		1xVGA 3xHDMI 1xPC audio 1xRS232C 1x IR 1xUSB(Media Player)
Player (USB) Pho (USB) Mu: Ope Con Power Con	vie	MPEG-2 MPEG-4
Ope Con Con Con	oto	JPEG PNG BMP
Power Con	sic	MP3
Power	erating Voltage	100 – 240VAC
Con	nsumption (typ.)	1280W (Without PC)
	nsumption per nits (max.)	0.37W
Hea	ating Unit	Typ: 600W (Max: 850W)
Aut	to Cooling System	Yes
Aut	to Heating System	Yes
Features Tem	npered Glass	8mm (AR)
Ant	ti Reflection Coating	Yes
Aut	to Brightness Sensor	Yes
Te	nperature (°C)	-30 ~ 50
	midity (%)	20 - 90
Operation Stor	rage (°C)	-40 ~ 60
OSE) Language	12 Lang
Approvals Ingi	ress Protection	IP65
Dimension Set	(W x H x D), inch mm	80.94 x 48.31 x 7.09 2056 x 1227 x 180 80.94 x 48.31 x 8.37 2056 x 1227 x 212.7 (with Wall Frame)
Weight Set	(lb kg)	485.02 220
Mounting		800 x 800 (M12)

$Specifications\ and\ design\ are\ subject\ to\ change\ without\ notice.\ See\ our\ website\ for\ detailed\ information.$

HEAD OFFICE - HYUNDAI IT CO., LTD.

5F, 36, Sangil-ro 10-gil, Gangdong-gu, Seoul, 05288 Korea Tel. +82 70 7008 0151 E-mail: ssoh@hyundaiit.com

HYUNDAI IT AMERICA TECH CORP

2033 Gateway Place 5th Floor San Jose, CA 95110, USA Tel. +1 408 627 4729 email:sales@hyundaita.com www.hyundaiit.com

FEATURES

All Weather Capable

Equipped with an intelligent cooling and heating system, HYUNDAI IT's Outdoor Displays are well suited for withstanding any weather conditions from -30°C to +50°C.

Sunlight Readable

HYUNDAI IT provides special displays which are based on the Optical Bonding for installatons in environment with the birghtest lightning conditions. Make your messages and images clear and readable under even bright sunlight.


Cost Effective Media Player

HYUNDAI IT's display serves in-built media player enables to play various range of content including video, images and photos.

Thanks to this solution, no need for an additional media player for cost and space efficiency.

DIMENSIONS

[Unit: mm[inch]]



UPDATE: MAR. 2023

HYUNDAI IBT GMBH

Carl-Zeiss-Str. 9 / 55129 Mainz, Germany Tel. +49(0) 6131 275 5350 email: info@hyundaiit.eu www.hyundaiit.eu