# HYUNDAI IT

Smartboard lpha

CLASS

MODEL

65"


S65UPAI

## An intuitively Easy Smart Board Solution

Our Smart board - displays, software, services and support all work together - giving you the tools to share information and ideas in visual and interactive way. With a smart board, your resources are at your fingertrips - whether you're in a meeting room, an R&D lab or the dealer shop.



## **HYUNDAI IT**



### **SPECIFICATIONS**

	Model	S65UPAI
Panel	Screen Size (diagonal)	65"
	Active Display Area (mm)	1428.48(H) x 803.52(V)
	Resolution	3840 x 2160 (QWUXGA)
	Aspect Ratio	16:9
	Display Colors	1.07B (8bit+FRC)
	Brightness (cd/m²; typ.)	410
	Contrast Ratio	1200:1
	Response Time (ms, GTG)	8
	Viewing Angle (H°/V°)	178°/178°
	Lifetime (hours)	50,000
Resolution	Monitor Timming(max)	3840 x 2160
Touch Screen	Touch Technology	Advanced Infra-red Touch frame
	Touch Accuracy (Typ.)	±1mm(middle 0ver 90% area)
	Touch Resolution	32768 x 32768
	Response Time (ms) (Typ.)	3.3
	Number of touch points	Windows 11/10/8 40 Points, Android 20 Points, Windows XP/Linux/MAC/Chrome 1 Point
	Interface	USB 2.0 compatible(full speed) HID compatible Plug & Play compatible
	Detection Method	Infrared Rays
	Operating Systems	Windows / Android / Mac OS X
Systems	CPU / GPU(3D)	A73x4 + A53x4 2.2GHz   Mali G52 MP8
	Main Chipset	A311D2
	Cores	Quad core A73+ Quad core A53
	OS	Android 13
	RAM / ROM	8GB / 64GB
Interface	Front	1xUSB3.0(PC)   1xUSB3.0(Android)   1xUSB Type-C(65W)
	Side	3xTouch USB   1xDP1.2-ln   2xHDMI2.0-ln   1xUSB Type-C   1xUSB2.0   2xUSB3.0
	Bottom	1xAudio-In   1xVGA   1xLAN In/Out   1xRS232-In   1xMic   1xHDMI Out   1xAudio-Out   1xSPDIF-Out
	SD Card Slot	128GB
	OPS Slot	Option
Hotkey	Touch Capacitance Method	9key (Option)
Features	Speaker	15W 8ohm x 2 (Front)
	Camera	8 Mega pixels
	WiFi6	Intel(R) Wi-Fi 6 AX201 160Mhz:PCIE protocol, To as WiFi and Hotspot simultaneously
	Array Mic	8-mic
	Tempered Glass	3.2T (Anti Glare) Dry Bonding
	Auto Power Control (DPMS)	Yes
Operation	Temperature (°C)	0 - 40
	Humidity (%)	20 - 80
Power	Input Voltage	AC 100 ~ 240 V, 50/60Hz
	Power consumption	300W
Wall Mounting		600 x 400 (M8)
Dimension	Set (W x H x D) mm   in	1482.1 x 936.7 x 105.6   58.35 x 36.88 x 4.16 (without Wall Frame)
Weight	Set (kg   lb)	42   92.59
	1 (31)	Optional Stand
		1285 x 1760 x 700   50.59 x 69.29 x 27.56

## **CORPORATE SOLUTIONS**

#### **Design Engineering**

HYUNDAL IT smart board Solutions make it easy to review project materials and work with other resources on a large interactive surface. You share information visually, whether your teams are local or dispersed.

### **Business Process Management**

HYUNDAI IT smart board Solutions can help stakeholders and process owners collabrate to support agile development principles - from definition and analysis to activity mapping, improvement targets and ongoing measurement.

## Product development


HYUNDAI IT smart board Solutions, you can bring expects together in one room, regardless of location. You can work with file and applications on a large interactive and contribute to the work in real time.

#### Training

With HYUNDAI IT smart board Solutions, trainers can display and work with information on a large, interactive surface. And because our products are interactive, training participants can be involved in working with the material, making annotations and navigating the content themslves.

## **DIMENSIONS**

[unit: mm[inch]]



Specifications and design are subject to change without notice. See our website for detailed information.

UPDATE: DEC. 202

## HEAD OFFICE - HYUNDAI IT CO., LTD.

5F, 36, Sangil-ro 10-gil, Gangdong-gu, Seoul, 05288 Korea Tel. +82 70 7008 0151 E-mail: ssoh@hyundaiit.com

#### HYUNDAI IT AMERICA TECH CORP

2033 Gateway Place 5th Floor San Jose, CA 95110, USA Tel. +1 408 627 4729 email: sales@hyundaita.com www.hyundaiit.com

#### HYUNDAI IBT GMBH

Carl-Zeiss-Str. 9 / 55129 Mainz, Germany Tel. +49(0) 6131 275 5350 email: info@hyundaiit.eu www.hyundaiit.eu