HYUNDAI IT

HYUNDAI IT

Smartboard α



An intuitively Easy Smart Board Solution

Our Smart board - displays, software, services and support all work together - giving you the tools to share information and ideas in visual and interactive way. With a smart board, your resources are at your fingertrips - whether you're in a meeting room, an R&D lab or the dealer shop.



SPECIFICATIONS

	Model	S86UNAI
	Screen Size (diagonal)	86″
Panel	Active Display Area (mm)	1895.04(H) x 1065.96(V)
	Resolution	3840 x 2160 (QWUXGA)
	Aspect Ratio	16:9
	Display Colors	1.07B
	Brightness (cd/m ² ; typ.)	410
	Contrast Ratio	1200:1
	Response Time (ms, GTG)	8
	Viewing Angle (H°/V°)	178°/178°
	Lifetime (hours)	50,000
Resolution	Monitor Timming(max)	3840 x 2160
Touch Screen	Touch Technology	Advanced Infared Rays
	Touch Accuracy (Typ.)	±1.0mm
	Touch Resolution	32768 x 32768
	Response Time (ms) (Typ.)	3
	Multi Touch	Windows 11/10/8 40 Points, Android 20 Points, Windows XP/Linux/
	Interface	USB 2.0 compatible(full speed) HID compatible Plug & Pla
	Detection Method	Infrared Rays
	Operating Systems	Windows / Android / Mac OS X
Systems	CPU / GPU(3D)	A73x4 + A53x4 2.2GHz Mali G52 MP8
	Main Chipset	A311D2
	Architecture / Cores	Cortex A73+A53 A73x4 + A53x4
	OS	Android 13
	RAM(DDR)	8GB
	ROM	64GB
Interface	Front	1xHDMI2.0-In 1xUSB3.0(PC) 1xUSB3.0(Android) 1xUSB3.0(Touch)
	Side	3xUSB3.0(Touch) 1xUSB2.0 2xUSB3.0 1xUSB Type-C 1xDP1.2
	Bottom	1xHDMI-Out 1xSPDIF-Out 2xLAN In/Out 1xRS232-In 1xAudio-Out 1xPC
	OPS Slot / SD Card Slot	Option
Hotkey	Touch Capacitance Method	9key (Option)
Features	Speaker	15W 8ohm x 2 (Front)
	WiFi6	Intel(R) Wi-Fi 6 AX201 160Mhz:PCIE protocol, To as WiFi and Hot
	Tempered Glass	3.2T (Anti Glare) Dry Bonding
	Sharing / Eshare split	1/9
	Auto Power Control (DPMS)	Yes
Operation	Temperature (°C)	0 - 40
	Humidity (%)	20 - 80
Power	Input Voltage	AC 100 ~ 240 V, 50/60Hz
	Power consumption	460W
Wall Mounting (WxH), mm		800 x 600 (M8)
Dimension	Set (W x H x D) mm in	1961.9 x 1169.9 x 87.7 77.24 x 46.06 x 3.45 (without
Weight	Set (kg lb)	77 169.76
		Optional Stand
Mayabla Stan	d Set (W x H x D) mm in	1285 x 1760 x 700 50.59 x 69.29 x 27.56

Specifications and design are subject to change without notice. See our website for detailed information.

HEAD OFFICE - HYUNDAI IT CO., LTD. 5F, 36, Sangil-ro 10-gil, Gangdong-gu, Seoul, 05288 Korea

Tel. +82 70 7008 0151 E-mail: ssoh@hyundaiit.com www.hyundaiit.com

HYUNDAI IT AMERICA TECH CORP 2033 Gateway Place 5th Floor San Jose, CA 95110, USA Tel. +1 408 627 4729 email : sales@hyundaita.com www.hyundaiit.com

Smartboard α

CLASS

86″

S86UNAI

CORPORATE SOLUTIONS

Design Engineering

HYUNDAI IT smart board Solutions make it easy to review project materials and work with other resources on a large interactive surface. You share information visually, whether your teams are local or dispersed.

Business Process Management

HYUNDAI IT smart board Solutions can help stakeholders and process owners collabrate to support agile development principles - from definition and analysis to activity mapping, improvement targets and ongoing measurement.


Product development


HYUNDAI IT smart board Solutions, you can bring expects together in one room, regardless of location. You can work with file and applications on a large interactive and contribute to the work in real time.

Training

With HYUNDAI IT smart board Solutions, trainers can display and work with information on a large, interactive surface. And because our products are interactive, training participants can be involved in working with the material, making annotations and navigating the content themslves.

DIMENSIONS





HYUNDAI IBT GMBH

Carl-Zeiss-Str. 9 / 55129 Mainz, Germany Tel. +49(0) 6131 275 5350 email : info@hyundaiit.eu www.hyundaiit.eu

UPDATE: JAN. 2024

x/MAC/Chrome 1 Point lay compatible

) | 1xUSB Type-C(65W) .2-In | 2xHDMI2.0-In PC-Audio | 1xVGA | 1xMic

tspot simultaneously

Wall Frame)